


# WattmonPRO Overview

 This page provides an introduction to the features of the WattmonPRO.

## Wiring and Connections Diagram



## Power Requirements

WattmonPRO can run on a DC power source between 6 and 60V DC. It has a built in high efficiency switching buck regulator that ensures that it consumes less than 2 watts of power without accessory devices. The device can be shipped with an AC adapter or a DC power cable to be directly connected to your battery bank of up to 48V DC.

## Connectivity

WattmonPRO has two ways of connecting to the Internet. The built-in LAN can be connected directly to a laptop or router, and is used for setup and local monitoring (but can also be used for remote monitoring if the site has an Internet connection). The USB Host port works with a selected number of USB Cellular dongles (GPRS and 3G), allowing both outbound and inbound data via the Internet. Although we provide instructions on configuring your local dongle, not all of them work. Need a compatible USB dongle for remote monitoring? Use one of our Huawei dongles, the E303F or E3531.

## Hardware Features

### Serial (RS-232)

An [RS-232 serial port](#) allows you to interface with Inverters or other devices that can provide data. Drivers for Studer and Victron inverters are now provided along with the Wattmon, making it simple to remotely monitor your PV panels and energy information from the inverter itself.

### Modbus RTU (RS-485)

An RS-485 Modbus RTU interface is built in and Wattmon acts as a Modbus master to collect data from various devices such as power meters, current sensors, etc.

If you are planning to monitor a battery bank with Wattmon, you will require a current sensor device such as the C252 (25A) or C1002 (100A).

## Inputs and Outputs

The inputs and outputs and their various applications are described below.

### 4 digital inputs

Pins 16-19 are digital inputs. They are opto-isolated and can handle anywhere between 4 and 24V DC between the input pin and the DIGND pin. Pins 16-18 (DI1-DI3) can also be configured as pulse/frequency counters for measuring data from flow meters/anemometers, etc.

### 4 digital outputs

These are open collector type (using a ULN2003 chip) and can be directly connected to 12V relays (with external power supply) to control high power loads - they can handle up to 500mA per pin.

### Onboard relay

An on-board latching relay can switch DC or AC loads of up to 5 A. If higher loads are required, this relay can be used to power a larger one. The latching relay takes very little power to switch state and no power once toggled, so there is no difference in power draw whether the relay is on or off.

### 3 Analog inputs

WattmonPRO has three analog input channels, each with a 10-bit ADC on board (1024 possible values for the full scale).

A1 also doubles as the voltage supply for the device. This is done so that when the device is running from a battery it's possible to measure the battery voltage directly from the supply. Max voltage is 60V DC.

A2 is a voltage sense input that can be used to measure up to 330V DC for high voltage battery banks. The negative voltage terminal is shared with the main ground on pin 1.

A3 is used to measure up to 5V DC, perfect for sensor inputs from devices such as the PYRA300 Solar Irradiation Sensor or pH meters.

### OneWire Bus

WattmonPRO has a Dallas OneWire bus that allows for DS18B20 temperature sensors to be connected. This can be used for ambient or battery temperature measurement. You can connect up to 8 sensors per device. See here for more information:

<http://wattmon.com/9-user-guide/113-onewire-temperature-sensor>

## Storage

A removable/replaceable 4 or 8 GB MicroSD Card contains the OS, configuration and data log files (enough space for many years of logged values, every minute). The SD Card uses a standard format (FAT32) that is read/write compatible with Windows and other computers and devices.

WattmonPRO has 128 KB RAM (enough space for about 30 KB of added user variables and scripts).

There is also 8 KB of NVRAM for storing configuration and other data that needs to be available after a power loss or reboot.

## Standards Compliance

WattmonPRO is classified as a device for Industrial use. The device complies with the following standards:

- **IEC-61000-4-2** - Electrostatic Discharge
- **IEC-61000-4-4** - EFT Immunity - 1kV
- **IEC 61000-4-5** - EMC Immunity - 1kV
- **CISPR 11 Class A** - EMC

From:  
<http://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:  
[http://wattmon.com/dokuwiki/hardware/wattmons/wattmonpro\\_intro?rev=1535892555](http://wattmon.com/dokuwiki/hardware/wattmons/wattmonpro_intro?rev=1535892555)

Last update: **2021/09/13 05:56**

