

explode

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Turn a string into an array

Description

`array explode (string $value, string $delimiter)`

Turn a string into an array by separating out the elements as bounded by a delimiter character

Parameters

value: String to be separated into elements in the array

delimiter: Character to use for separation

Return Value

Array of elements

Example

```
<pre><?
    $mylist="one,two,three,four";
    $myarray=explode($mylist,",");
    print_r($myarray);
?></pre>
```

The above example will output:

```
[$myarray] = Array (
    (string) [0] => one
    (string) [1] => two
    (string) [2] => three
    (string) [3] => four
)
```

See Also

[implode\(\)](#) - Turn an array into a string

[print_r\(\)](#) - Dump the contents of an array to the current output

[sizeof\(\)](#) - Return the number of elements in an array

[uPHP Variable Types and Limits](#)

Additional Information

Note that there is an important difference in the parameter order between mainline PHP and Wattmon uPHP. In the mainline PHP function the delimiter comes first, but in uPHP the string to be exploded comes first:

PHP `explode(delimiter, string)`

uPHP `explode(string, delimiter)`

Wattmon uPHP's parameter order is easier to remember and more consistent: The delimiter parameter comes last in both [explode\(\)](#) and [implode\(\)](#).

From:

<http://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

<http://wattmon.com/dokuwiki/uphp/functions/explode?rev=1490644215>

Last update: **2021/09/13 05:56**

