

# ftell

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Position the file pointer in an open file

## Description

`ftell ( int $handle, int $offset, int $whence )`

This function will relocate the file pointer within an active file. Three different start position options are available.

## Parameters

**\$handle**: Valid handle of a previously opened resource

**\$offset**: How far to move the pointer (bytes)

**\$whence**: Seek type, starting position option, from where to move the pointer:

- **0** - Seek from the **start of the file**
- **1** - Seek from the **current position**
- **2** - Seek from the **end of the file** (in reverse)

## Return Values

None

## Example

```
<?
$fp=fopen("/index.cgi","r");
if ($fp) {
    fseek($fp,10,2); // position to 10 characters before the end of the file
    $data=fread($fp,10);
    print($data);
    fclose($fp);
} else {
    print("File open failed\n");
}
?>
```

## See Also

[fopen\(\)](#) - Open a file for reading or writing

[fread\(\)](#) - Return bytes from a file or stream

[fgets\(\)](#) - Return a single line from a file or stream, with optional size limit

[fwrite\(\)](#) - Write data to a file or stream

[fclose\(\)](#) - Close a file, stream or socket

From:

<http://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

<http://wattmon.com/dokuwiki/uphp/functions/ftell?rev=1490967808>

Last update: **2021/09/13 05:56**

