

ini_set

WMPRO, WMMINI FW >= 1.0 WMMEGA FW >= 2.0

Set a value in an INI file

Description

```
int ini_set ( string $filename, string $section, string $key, mixed $value )
```

This function writes a configuration key/value pair to an INI file.

If the INI file does not already exist it is created with the given **section**, **key** and **value**. However, if the INI file already exists it is updated only for the specified **section**, **key** and **value**, which preserves any other information, sections, keys or values that might be in the file to begin with.

If the **section** does not exist it is appended to the end of the file along with the **key** and **value**.

If the **key** does not exist it is added to the **section**, if it exists, otherwise the **section**, **key** and **value** are appended to the end of the file.

Parameters

\$filename: Full path and name of the INI file

\$section: Name of the section inside the INI file

\$key: Name of the key inside the **section**

\$value: The value to write (**string**, **int** or **float**)

Return Value

Integer: 1 on success or 0 on failure

Example

```
<?
$fn="/ini_set_example.ini";
ini_set($fn,"network","address1","90.0.0.1");
ini_set($fn,"general","enabled",1);
ini_set($fn,"general","connected",0);
/* ... get connected ... */
ini_set($fn,"general","connected",1);
```

```
?>
```

The INI file will contain:

```
[network]
address1=90.0.0.1
[general]
enabled=1
connected=1
```

See Also

[ini_get\(\)](#) - Get a value from an INI file

[ini_get_array\(\)](#) - Get a group of parameters from an INI file as an **array**

[ini_put_array\(\)](#) - Write a group of parameters to an INI file from an **array**

From:

<http://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

http://wattmon.com/dokuwiki/uphp/functions/ini_set?rev=1494324459

Last update: **2021/09/13 05:56**

