

mqtt_subscribe

WMPRO, WMMINI FW >= 1.1074 WMMEGA FW >= 2.1078

Subscribe to an MQTT channel

Description

`mqtt_subscribe (string $channel, string $callback)`

Parameters

\$channel: Channel to subscribe to. See [MQTT Configuration](#)

\$callback: Callback script to execute upon receipt of a message

Return Values

1 if successful and 0 on failure

Example

```
<?
// Use the # as a wildcard so any messages to /cluster/1/ or its sub
channels will be received

mqtt_subscribe("/cluster/1/#", "/scripts/tests/mqttsub.cgi");
?>
```

Example Callback

Callbacks can use the `stdin` file to read input. Use `fgets()` to get the first line, which will be the full channel. The following lines will be the data received.

```
<?
$f=fopen("php://stdin","r");
$st=fgets($f);
$msg=fgets($f);
$response="";
if (substr($msg,0,3)=='get') {
    $variable=substr($msg,4,strlen($msg)-3);
    $response=$variable.":".$_GLOBALS[$variable];
```

```
}

if (strpos($st, getmac()) || strpos($st, '/all')) {
    if (strpos($st, "get")) {
        mqtt_publish("/cluster/1/ret/".getmac(), $response);
    } else {
        if (strpos($st, "ret")) {
            print("Notification was properly posted");
        }
    }
}
?>
```

Note

On WattmonPRO & MINI the maximum packet size is 128 bytes. On WattmonMega, M2 & Mini2 the maximum packet size is 2048 bytes.

See Also

[mqtt_publish\(\)](#) - Publish to an MQTT channel

From:
<http://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**



Permanent link:
http://wattmon.com/dokuwiki/uphp/functions/mqtt_subscribe?rev=1575004329

Last update: **2021/09/13 05:56**