

# WattmonMINI3-4G

Remote Monitoring & Control Solution



## Specifications

### Communication

- RS-485 Modbus RTU port for communication with up to 15 Slaves
- Modbus TCP Client mode for communication with up to 10 Servers
- Modbus TCP Server mode to interface with SCADA systems

### Inputs & Outputs

- One Analog Input (6-60V DC) on Supply Voltage

### Power

- Input voltage range: 6-60V DC
- High Efficiency DC-DC converter
- Low Power Consumption of < 4 Watts

### Network

- 100 Mbit Ethernet
- 4G LTE | Nano-SIM

### Storage

- 512 KB RAM
- 16 GB MicroSD Card

### Data Collection & Export

- CSV format
- HTTP / HTTPS / FTP / SFTP / MQTT / MQTTS

## Applications

- **Inverter Monitoring**  
Inspect generation and efficiency of grid-tie and hybrid inverters.
- **AC/DC Power Monitoring**  
Supervise load and performance of substations and mini-grids, and monitor battery voltage natively.
- **Weather Station Monitoring**  
Observe irradiation, temperature and other atmospheric conditions.
- **Zero Feed-In & DG Protection**  
Reduce active output power of multiple inverters to regulate energy generation.

## Characteristics

Enclosure Material	Polyamide, UL 94 V0
Enclosure Colour	Light Grey, similar to RAL 7035
Degree of Protection	IP20 (Finger Protected)
Operating Temperature	0-60 °C
DIN Standard Mount	DIN EN 60529
Dimensions (L x W x H)	105 x 23 x 115 mm
Weight	170 g

## Introduction

The Wattmon hardware and software platform is the most flexible in the industry. It can be used for monitoring Grid-Tie, Hybrid and Off-Grid setups, Solar Water Pumping, Building Loads, and features a Zero Feed-In and DG Protection solution that is compatible with leading manufacturers.

The WattmonMINI3-4G is a Modbus Master (Modbus TCP Client) that can interface with up to 15 RTU Slaves and 10 TCP Servers. It may also be configured as a Modbus TCP Server to interface with a SCADA system. A quick configuration tool allows for the setting up of the device for a range of inverters, energy meters and sensors.

It supports the following data types:

- IEEE754 Float (Big and Little Endian)
- INT32 (Big and Little Endian)
- UINT32 (Big and Little Endian)
- INT16

## Benefits

- **Versatile**  
Configurable by anyone using the built-in *EZConfig* function
- **Multilingual**  
Features an interface in English, Español, Deutsch, Français, हिन्दी, தமிழ்
- **Remotely Accessible**  
Log into the device remotely through the Wattmon Proxy server using a 3G/4G SIM Card or via Ethernet
- **Industry Compliant**  
Integrate new and existing devices over Modbus RTU/TCP with the on-board device driver creator
- **Local Storage**  
Securely store several years worth of data locally in CSV format and control who can view it
- **Programmable**  
Write scripts in the built-in editor using the uPHP language or the *Visual Script Builder*

## Zero Feed-In & DG Protection

The Wattmon Power Control Solution can throttle the active power output of inverters on sites with no Net Metering or with Diesel Generators, securing against grid export or reverse-feeding and over-frequency damage. The supported brands are :

- |            |                      |
|------------|----------------------|
| ■ ABB      | ■ Polycab            |
| ■ Delta    | ■ Refusol            |
| ■ Emerson  | ■ SofarSolar         |
| ■ Fronius  | ■ Schneider          |
| ■ Goodwe   | ■ SMA                |
| ■ Growatt  | ■ SolarEdge          |
| ■ Huawei   | ■ Solis Ginlong      |
| ■ Ingeteam | ■ Sungrow            |
| ■ Kaco     | ■ Zeversolar         |
| ■ Kstar    | ■ <i>and more...</i> |

## Energy Monitoring Solution (EMS)

The WattmonMINI3-4G is capable of storing several years worth of data on the MicroSD card. It can also upload the logged data to the Wattmon Energy Monitoring Solution (EMS), a highly customizable cloud portal that displays real-time data in the form of graphs and widgets, allowing users to select the parameters they wish to monitor, and create separate accounts for individual clients.

## Conformity

Radiated Emissions	
Conducted Emissions	
RoHS	

Copyright © 2021  
 Cynergy  
 Maitreye, Auroville  
 605 101 Tamil Nadu, India  
 Phone: +91 413 262 2059  
 Website: <http://www.wattmon.com>