

# call\_user\_func

WMPRO, WMMINI FW > 1.0 WMMEGA FW > 2.0

Call a user defined function with optional parameters

## Description

`mixed call_user_func ( string $function_name [, mixed $parameters ... ] )`

Return result as defined by the user function

## Parameters

**function\_name**: String containing the name of the user function to call

**parameters**: Optional parameters to pass to the function

## Return Value

Any type depending on the way the function is defined

## Example

```
<?
function my_add($x,$y) {
    return $x+$y;
}
$result=call_user_func("my_add",1,3);
print($result); // result is 4
?>
```

## See Also

[function](#) - Define a function

[return](#) - Return program control to the calling module

[print\(\)](#) - Output data to the current output stream such as a web page or terminal

## Additional Information

User defined functions can take many different forms, and it is not necessary to use [call\\_user\\_func\(\)](#)

to execute a function unless a direct return value is needed.

If used within a function, the **return** statement immediately ends execution of the function, and returns its argument as the value of the function call.

From:

<https://wattmon.com/dokuwiki/> - **Wattmon Documentation Wiki**

Permanent link:

[https://wattmon.com/dokuwiki/uphp/functions/call\\_user\\_func?rev=1487428352](https://wattmon.com/dokuwiki/uphp/functions/call_user_func?rev=1487428352)

Last update: **2021/09/13 05:56**

